



OPEN FOR YOUR HOME DECORATING IDEAS

Kömmerling PremiSlide 76

FUNCTIONALITY FOR SPACIOUS VIEWS

The sliding system with comfort

Kömmerling PremiSlide 76 offers you a wide range of options for harmoniously integrating windows and doors into the façade. The sliding system also offers functional features for a variety of applications.

Whether with a PVC-U frame or a combined frame made of PVC-U and aluminium – Kömmerling PremiSlide 76 can be manufactured in both variants. With its installation depth of 76 mm, this sliding system proves its worth not only in residential spaces but also in public buildings such as schools or office blocks. The operating mechanism is provided by ECO SLIDE, the user-friendly sliding fitting from our partner Siegenia. Kömmerling PremiSlide 76 also offers good thermal insulation performance – depending on the version and glazing.

> GOOD THERMAL INSULATION VALUE

Energy performance: Even in its standard version, Kömmerling PremiSlide 76 achieves an U_f value of up to $1.4 \text{ W/(m}^2\text{K)}$

> STABLE GLAZING

Triple glazing with a thickness of up to 50 mm.

> FUNCTIONALITY

Functional safety and structural integrity are ensured by appropriately dimensioned steel reinforcements and welded corner connectors

> ELEGANT DESIGN

In both the fixed and sliding parts, Kömmerling PremiSlide 76 is characterised by a slender profile sight line.

> INNOVATIVE TECHNOLOGY

The design is based on the Kömmerling 76 double seal system, combined with the user-friendly and nonwearing ECO SLIDE hardware system.

> EFFECTIVE VENTILATION

The ECO SLIDE carriage provides the basis for individual gap ventilation.

> Space-saving opening

> Large glazed areas

> Wide design spectrum

> Effective ventilation

U_w value
up to
0.70
 $\text{W/(m}^2\text{K)}$



EASY OPERATION THANKS TO SLIDING MECHANISM

ECO SLIDE the high-quality sliding fitting from Siegenia

Easy opening, controlled deceleration, gentle closing – this is how Kömmerling PremiSlide 76 works, thanks to the smooth-running carriages of the ECO SLIDE sliding hardware. This is because they absorb the closing movement of the sashes through a sideways movement and ensure a gliding action. Shortly before reaching the end position, the sash is slowed by the SOFT CLOSE damper and then drawn into the closed position almost as if by itself. This can relieve the strain on the sliding elements and reduce the risk of injury when closing.



- **Versatile:** For practical sliding windows and lightweight sliding doors
- **User-friendly operation:** For a smooth and nonwearing locking movement
- **Can be combined with the SOFT CLOSE damper:** For smooth sliding into the fastening position





COLOUR AND DESIGN OF YOUR CHOICE

Classic PVC-U white or striking plain tones? Exclusive metallic colours or wood look? Or how about AluClip, the variant with a sophisticated aluminium cladding? Kömmerling PremiSlide 76 offers you a wide range of design options.



Kömmerling PremiSlide 76
Standard laminated with
PVC-U frame



Kömmerling PremiSlide 76
AluClip with PVC-U frame



Kömmerling PremiSlide 76
Standard laminated with
combined outer frame
made of PVC-U and aluminium



Kömmerling PremiSlide 76
AluClip with combined
outer frame made of PVC-U
and aluminium

#KömmerlingForTomorrow

profine GmbH
Kömmerling

Zweibrücker Straße 200
66954 Pirmasens
Tel. +49 (0) 6331 560
E-mail: info@koemmerling.com

www.koemmerling.com

